


PRODUCT SPECIFICATION SUPALOX N4

PRODUCT	High Purity Aluminum Oxide, Al ₂ O ₃	PURITY	> 99.99%
---------	--	--------	----------


PARAMETERS	METHOD	SPECIFICATIONS
TYPICAL PHYSICAL PROPERTIES		
Appearance	Visual inspection	White Powder
Crystallinity	XRD	Alpha-alumina
D10	Laser Diffraction	0.5 µm
D50	Laser Diffraction	1 µm
D90	Laser Diffraction	3 µm
Moisture	2 hrs at 120°C	<1.0 %
Surface Area	N ₂ adsorption (BET)	<10 m ² /g
Tap Density	ASTM B527 – 06	> 0.80 g/cm ³



TYPICAL CHEMICAL COMPOSITION		
Na	ICP-MS	<40 ppm
Mg	ICP-MS	<5 ppm
Si	ICP-MS	<30 ppm
K	ICP-MS	<3 ppm
Ca	ICP-MS	<10 ppm
Fe	ICP-MS	<10 ppm



SUPALOX N4 is a spray dried, micron-sized alpha alumina product, designed for ceramics and industrial applications.



For technical information, please contact: info@aemcanada.com

Manufactured with virtually zero CO₂ emission in CANADA

The listed properties represent the typical measured values for this product may not represent the final properties of a given batch. Contact AEM for more information.